

SS,SH防球ネット柱間隔、使用柱早見表

	地表粗土区分Ⅱ						地表粗土区分Ⅲ					
	V0=30m/s		V0=32m/s		V0=34m/s		V0=30m/s		V0=32m/s		V0=34m/s	
地上高	最大柱間隔	使用柱	最大柱間隔	使用柱	最大柱間隔	使用柱	最大柱間隔	使用柱	最大柱間隔	使用柱	最大柱間隔	使用柱
H=4m	10m	7-19-3.5	13m	7-19-4.3	11m	7-19-4.3	18m	7-19-3.5	16m	7-19-3.5	14m	7-19-3.5
H=5m	11m	7-19-4.3	10m	7-19-4.3	12m	7-19-6	14m	7-19-3.5	12m	7-19-3.5	13m	7-19-4.3
H=6m	11m	8-19-5	11m	8-19-6	10m	8-19-6	14m	8-19-4.3	12m	8-19-4.3	11m	8-19-4.3
H=8m	11m	11-19-7	14m	11-19-10	12m	11-19-10	11m	11-19-5	14m	11-19-7	12m	11-19-7
H=10m	12m	13-19-10	10m	13-19-10	9m	13-19-10	12m	13-19-7	10m	13-19-7	10m	13-19-7
H=12m	10m	15-19-10	9m	15-19-10	8m	15-19-10	10m	15-19-7	14m	15-19-10	12m	15-19-10
H=14m	11m	17-22-15	10m	17-22-15	8m	17-22-15	11m	17-22-10	15m	17-22-15	13m	17-22-15
H=15m	15m	15-22-15	13m	15-22-15	11m	15-22-15	14m	15-22-10	12m	15-22-10	16m	15-22-10
		Φ600(2)-3		Φ600(2)-3		Φ600(2)-3		Φ600(2)-3		Φ600(2)-3		
H=20m	14m	25-30-20	12m	25-30-20	10m	25-30-20	20m	25-30-20	18m	25-30-20	15m	25-30-20
H=25m	12m	28-30-25	13m	28-30-30	11m	28-30-30	18m	28-30-25	16m	28-30-30	13m	28-30-30
		Φ900-9t-6m		Φ900-9t-6m		Φ900-9t-6m		Φ900-9t-6m				
H=30m	15m	30-35-35	12m	30-35-35	10m	30-35-35	20m	30-35-35	18m	30-35-35	16m	30-35-35
		Φ900-12t-8m		Φ900-12t-8m		Φ900-12t-8m		Φ900-12t-8m				

標準図面、積算条件